



LEDVANCE® HAZARDOUS LINEAR BAY

Luminaria LED para áreas clasificadas que, por su estructura de acero inoxidable y difusor de policarbonato de alta densidad, es ideal para montajes suspendidos o sobrepuestos de manera continua por medio de tubería Conduit.

LED luminaire for classified areas that, due to its stainless steel structure and high-density polycarbonate diffuser, is ideal for suspended or continuously superimposed assemblies using conduit pipe.



APLICACIONES / APPLICATIONS



Código Sku	Potencia Power (W)	Flujo Luminoso Luminous Flux (lm)	Voltaje Voltage (V)	Ángulo de Apertura Opening Angle	Temp. de Color Color Temp. (K)	Vida Útil L70 L70 Life (h)	Prueba Salina Saline Test	Clasificación - T T - Rating	Montaje NPT NPT Mounting
91115	40	6 000	100-277	120°	● 5000	100 000	1 000 h	T5 @ 50°C	¾"
91116	60	9 000	100-277	120°	● 5000	100 000	1 000 h	T5 @ 50°C	¾"
91117	40	6 000	277-480	120°	● 5000	100 000	1 000 h	T5 @ 50°C	¾"
91118	60	9 000	277-480	120°	● 5000	100 000	1 000 h	T5 @ 50°C	¾"